

# Technical Data Sheet



## Product Name:

EuroLite 10W-40

## Comma recommends this product for applications requiring:

MB 229.1; VW 501 01, VW 505 00

ACEA A3/B4; API SL CF

## Product Features:

- Semi synthetic, high performance, 10W-40 oil, suitable for petrol vehicles including those with fuel injected and multivalved engines.
- To ensure correct oil selection check Comma's latest Application guide in store or online at [www.CommaOil.com](http://www.CommaOil.com)

## Typical Inspection Data:

Specific gravity at 20°C	0.870
Viscosity @ 100°C	13.9 cSt
Viscosity @ 40°C	92 cSt
Viscosity Index	155
Viscosity CCS @ -25°C	6200 cP
T.B.N.	7.8 mg KOH/g
Sulphated Ash Mass	1.3%
Zinc	0.18%
Calcium	0.26%
Phosphorus	0.18%
Colour	Brown

## Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

## Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the day of the year, the last two figures the year.