



Typical Inspection Data:

Density @ 20°C	1.050 g/cm ³
Viscosity @ 100°C	2.3 cSt
Viscosity @ -40°C	1350 cSt
Colour	Colourless to amber
Equilibrium Boiling Point	270 °C
Wet Equilibrium Boiling Point	160 °C
pH	7.0 – 11.5

DOT 4

Synthetic Brake Fluid

Recommended by Comma for applications requiring:

FMVSS 116 DOT 4, ISO 4925 (Class 3 & 4), SAE J1704

Product Features:

- The current standard brake fluid for most manufacturers. Ideal for cars with ABS systems. Can be mixed safely with DOT 3 and DOT 4 fluids.
- Can be safely used to top-up systems containing FMVSS.116 DOT 3 or 4 and SAE J1703 fluids.

Directions for use:

- Important: - Follow vehicle manufacturer's recommendations.
- Damaging to paintwork.
- Prevent moisture absorption – only store in the original packaging.
- Do not allow any contamination – oil, water, fuel, dirt etc.
- All brake fluids absorb moisture and therefore they must be checked or changed regularly.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 3 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

14-11-2014