COMMA

Technical Data Sheet



Eco-FE 0W-30

Fully Synthetic

Recommended by Comma for applications requiring:

Ford WSS-M2C950-A
ACEA C2

Product Features:

- Fully synthetic, low-SAPS engine oil specifically developed for latest technology Ford engines from 2014 onwards.
- Designed for high fuel efficiency.
- Suitable for petrol and diesel vehicles.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

Typical Inspection Data:

Density @ 20^{0}C	0.838
Viscosity @ 100^{0}C	9.4 cSt
Viscosity @ 40^{0}C	47 cSt
Viscosity Index	195
Viscosity CCS @ -30^{0}C	5100 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.09%
Colour	Brown
Flash Point	>200°C
Pour Point	-45°C

11-04-2016

Comma Oil & Chemicals Ltd.
Dering Way, Gravesend, Kent DA12 2QX, England.
Tel: +44 (0)1474 564311, Fax: +44 (0)1474 333000
Email: sales@commaoil.com www.CommaOil.com