



EUROLITE 10w40 SEMI SYNTHETIC MOTOR OIL

APPLICATION

- Suitable for high performance engines including fuel injected and multivalve designs.
- Enhanced protection in all conditions - extremes of heat and cold.
- Provides Supreme performance.
- Synthetic blend to prolong engine life.
- Helps reduce emissions and protects catalytic converters.

SPECIFICATIONS

- SAE 10w40
- API SL, CF
- ACEA A3-02, B3-98#2
- MB 229.1
- VW 505.00

TYPICAL INSPECTION DATA

Specific gravity at 20°C	0.870
Viscosity @ 100°C	13.9 cSt
Viscosity @ 40°C	92 cSt
Viscosity Index	155
Viscosity CCS @ -25°C	6200 cP
T.B.N.	6.9 mg KOH/g
Sulphated Ash Mass	1.0%
Zinc	0.16%
Calcium	0.19%
Phosphorus	0.15%
Colour	Brown

HANDLING

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

SHELF LIFE

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.