



Product Name:

Syner-Z 5W-30

Comma recommends this product for applications requiring:

BMW LL-04; MB 229.31, MB 229.51;
VW 502 00, VW 505 00, VW 505 01; dexos 2

ACEA C3; API SM CF

Product Features:

- For modern BMW, Mercedes Benz and GM vehicles operating with longlife service intervals.
- Fully synthetic, high performance, 5W-30 low SAPS oil, specially formulated for modern petrol and diesel vehicles fitted with exhaust after-treatment units that require an ACEA C3 grade, including certain Chrysler, Honda, Hyundai, Kia and Nissan models.
- Do not mix this oil with other types of oil, as the requirement for the longlife service intervals and exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest Application guide in store or online at www.CommaOil.com

Typical Inspection Data:

Specific gravity at 20°C	0.848
Viscosity @ 100°C	12.0 cSt
Viscosity @ 40°C	70 cSt
Viscosity Index	165
Viscosity CCS @ -30°C	6400 cP
T.B.N.	6.7 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.08%
Colour	Brown

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the day of the year, the last two figures the year.