

Technical Data Sheet



Typical Inspection Data:

Density @ 20⁰C	1.124 g/cm3
Appearance	Clear violet liquid
Boiling point	Min 170ºC

Protection Levels:

Xstream® G30® (%)	Approx. Protection (°C)
33	-18
50	-36
60	-52

Xstream® G30® Antifreeze & Coolant Concentrate

Glysantin® G30® by BASF is approved by:

VW/Audi/Seat/Skoda/Bentley/Bugatti/Lamborghini (TL774-D/F); Jaguar from 1999 (VIN 878389); Porsche from 1996; MINI Cooper D between 2007 and 2010; DAF; MAN (324 SNF); MTU (MTL 5048) The Product also protects: Volvo Truck from 2006

This Engine Coolant Concentrate conforms to the requirements of: BS 6580:2010

Product Features:

- Ethylene glycol based antifreeze & coolant with OAT inhibitors.
- Protects against corrosion, overheating and freezing.
- Typical service life of up to 5 years.
- Safeguarded with bittering agent to help prevent accidental ingestion.
- To ensure correct antifreeze & coolant selection check Comma's latest application guide in store or online at www.CommaOil.com.

Directions for use:

- 1. Dilute with de-ionised water in accordance with the vehicle manufacturer's instructions.
- 2. Pour into vehicle cooling system.
- 3. Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook.
- 4. Remove spills from paintwork immediately.

Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.
- Wash off any spillage on paintwork immediately.
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

14-11-2014

Comma Oil & Chemicals Ltd.

Dering Way, Gravesend, Kent DA12 2QX, England. Tel: +44 (0)1474 564311, Fax: +44 (0)1474 333000 Email: sales@commaoil.com www.CommaOil.com