



## **X-FLOW TYPE PD 5w40 FULLY SYNTHETIC MOTOR OIL**

### **APPLICATION**

- Suitable for Volkswagen Audi Group diesel engines employing the "Pumpe Duse" system with Unit Injectors operating under standard oil drain intervals.
- Also suitable for other applications requiring a 5W40 A3/B3 or A3/B4 product
- Ultimate protection in all conditions - extremes of heat and cold.
- Fully synthetic to prolong engine life.

### **SPECIFICATIONS**

- SAE 5w40
- API SL, CF
- ACEA A3/B3, A3/B4
- VW 505.01
- Ford WSS M2C917-A

### **TYPICAL INSPECTION DATA**

Specific gravity at 20°C	0.850
Viscosity @ 100°C	14.1 cSt
Viscosity @ 40°C	86 cSt
Viscosity Index	160
Viscosity CCS @ -30°C	6400 cP
T.B.N.	7.0 mg KOH/g
Sulphated Ash Mass	1.0%
Zinc	0.10%
Calcium	0.16%
Phosphorus	0.09%
Colour	Brown

### **HANDLING**

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### **SHELF LIFE**

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.