



Typical Inspection Data:

Density @ 20°C	0.847
Viscosity @ 100°C	12.0 cSt
Viscosity @ 40°C	70 cSt
Viscosity Index	165
Viscosity CCS @ -30°C	6200 cP
T.B.N.	7.3 mg KOH/g
Sulphated Ash Mass	0.49%
Zinc	0.06%
Phosphorus	0.05%
Colour	Brown
Flash Point	230°C
Pour Point	-42°C

Ecoren 5W-30

Fully Synthetic

Official Approvals:

Approved by Renault to meet RN0720

Recommended by Comma for applications requiring:

RN0720; MB 226.51
ACEA C4

Product Features:

- Fully synthetic, high performance 5W-30 low SAPS oil for modern petrol and diesel vehicles including those fitted with exhaust after-treatment units that require an ACEA C4 grade.
- Do not mix this oil with other Types of oil, as the requirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

21-07-2016