



## Typical Inspection Data:

Density at 20°C	0.848
Viscosity @ 100°C	11.7 cSt
Viscosity @ 40°C	68 cSt
Viscosity Index	170
Viscosity CCS @ -30°C	6200 cP
T.B.N.	5.5 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.08%
Calcium	0.15%
Phosphorus	0.07%
Colour	Brown
Flash Point	230°C
Pour Point	-36°C

## Prolife 5W-30

Fully Synthetic

### Recommended by Comma for applications requiring:

VW 504 00, VW 507 00; MB 229.51; BMW LL-04;  
PORSCHE C30

ACEA C3

### Product Features:

- Fully synthetic, high performance 5W-30 low SAPS oil, for modern VW-Audi group petrol and diesel vehicles including those operating under long life service regimes. Also protects exhaust after-treatment units.
- Do not mix this oil with other types of oil, as the requirement for the longlife service intervals and exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest Application guide in store or online at [CommaOil.com](http://CommaOil.com)

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

md 09-12-2013