



## Typical Inspection Data:

Density @ 20 °C	0.842 g/cm <sup>3</sup>
Viscosity @ 100 °C	9.1 cSt
Viscosity @ 40 °C	48 cSt
Viscosity Index	180
Viscosity CCS @ -35 °C	5600 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.19%
Phosphorus	0.09%
Colour	Amber
Flash Point	>200 °C
Pour Point	-42 °C

## Eco-V 0W-20

Fully Synthetic

### Official Approvals:

Officially approved by Volvo to meet VCC RBS0-2AE

### Recommended by Comma for applications requiring:

ACEA A1/B1

### Product Features:

- Fully synthetic engine oil specifically developed for latest technology Volvo engines from 2013 onwards.
- Designed for high fuel efficiency.
- Suitable for petrol and diesel vehicles.
- To ensure correct oil selection use Comma's latest application guide instore or online at [www.CommaOil.com](http://www.CommaOil.com).

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

24-02-2017