



Typical Inspection Data:

Density @ 20 °C	0.850 g/cm ³
Viscosity @ 100 °C	12.2 cSt
Viscosity @ 40 °C	70 cSt
Viscosity Index	165
Viscosity CCS @ -30 °C	6000 cP
T.B.N.	6.4 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.08%
Colour	Brown
Flash Point	230 °C
Pour Point	-39 °C

Syner-Z 5W-30

Fully Synthetic

Official approvals:

MB 229.31, MB 229.51, MB 229.52

Recommended by Comma for applications requiring:

BMW LL-04; VW 502 00, VW 505 00, VW 505 01, dexos 2
ACEA C3; API SN CF

Product Features:

- Fully synthetic, high performance 5W-30 low SAPS oil for modern petrol and diesel vehicles including those fitted with exhaust after-treatment units that require an ACEA C3 grade.
- For modern BMW, MB and GM vehicles including those operating with long life service intervals.
- Do not mix this oil with other types of oil, as the requirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

24-02-2017