

## **Technical** Data Sheet



#### **Typical Inspection Data:** Density @ 20 °C 0.842 g/cm3 Viscosity @ 100 °C 10.2 cSt Viscosity @ 40 °C 55 cSt Viscosity Index 180 Viscosity CCS @ -35 °C 6000 cP T.B.N. 8.0 mg KOH/g **Sulphated Ash Mass** 1.1% Zinc 0.11% Calcium 0.26% **Phosphorus** 0.11% Colour Brown **Flash Point** 230 °C **Pour Point** -45 °C

# Voltech 0W-30

Fully Synthetic

Recommended by Comma for applications requiring:

ACEA A5/B5; API SL

#### **Product Features:**

- Fully synthetic, high performance 0W-30 oil, for modern Volvo petrol and diesel vehicles.
  Offers improved fuel economy benefits of an ACEA A5/B5 oil
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

#### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### **Shelf Life:**

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

24-02-2017