

Technical Data Sheet



Physical Properties:

_							
Α	n	p	ea	ra	n	C	е

Red and Grey
semi-viscous liquids
with the
Grey Primer characteristic paint
solvent odours

Black Gloss

Matt Black Cloured liquids with
characteristic paint
solvent odour

Silver Wheels

Spray Paints

Product Features:

 Spray paints are available as primers and as gloss or matt finishes for coating any metallic surface.

Finishes Available:

- · Red oxide primer
- Grey primer
- Black gloss
- Matt black
- Satin black
- Silver wheels

Directions for use:

- 1. Ensure surface is free from rust, dirt, grease and wax.
- 2. Shake can well before use.
- 3. Apply evenly, holding can vertically around 30cm from the surface.
- 4. Ensure paint is touch-dry before reapplying. To clear valve turn cap upside down and spray until gas is emitted.

Handling:

- Caution pressurized container: protect from sunlight and other heat sources.
- Refer to Material Safety Data Sheet.

Volatile Organic Content:

- The EU limit value for these products (product category IIB e) in ready to use form is max 840 g/litre of VOC.
- The typical VOC content of these products in ready to use form is 625 - 675 g/litre.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

20-11-2014