



Typical Inspection Data:

Density @ 20 °C	0.850 g/cm ³
Viscosity @ 100 °C	13.5 cSt
Viscosity @ 40 °C	78 cSt
Viscosity Index	160
Viscosity CCS @ -30 °C	6000 cP
T.B.N.	7.2 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.09%
Colour	Brown
Flash Point	230 °C
Pour Point	-39 °C

PD Plus 5W-40

Fully Synthetic

Recommended by Comma for applications requiring:

VW 505 01, FORD WSS M2C917-A; VW 502 00, VW 505 00; BMW LL-04; MB 229.31, MB 229.51; dexos 2; Porsche A40
ACEA C3; API SN CF

Product Features:

- For VW PD/unit injector engines operating on fixed service intervals.
- Fully synthetic, high performance, 5W-40 oil, for vehicles fitted with the VW 'Pumpe Düse' PD or unit injector engine. Also protects exhaust after-treatment units.
- Do not mix this oil with other types of oil as the exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

24-02-2017