



Typical Inspection Data:

Density @ 20°C	1.124 g/cm ³
Appearance	Clear violet liquid
Boiling point	Min 170°C

Protection Levels:

Xstream® G40® (%)	Approx. Protection (°C)
33	-18
50	-36
60	-52

Xstream® G40® Antifreeze & Coolant Concentrate

Glystantin® G40® by BASF is approved by:

VW/Audi/Seat/Skoda/Bentley/Bugatti/Lamborghini (TL774-G) from 2005 onwards & Porsche 911, Boxster, Cayman, Cayenne, Panamera from 1997 onwards; Mercedes-Benz (325.6); MAN from 12/2011 (MAN 324 Typ Si-OAT); Mercedes Trucks from 10/2011 (325.5)

This Engine Coolant Concentrate conforms to the requirements of: BS 6580:2010

Product Features:

- Ethylene glycol based antifreeze with Si-OAT (Silicated Organic Additive Technology) inhibitors.
- Protects against corrosion, overheating and freezing.
- Typical service life of up to 5 years.
- Safeguarded with bittering agent to help prevent accidental ingestion.
- To ensure correct antifreeze & coolant selection check Comma's latest application guide in store or online at www.CommaOil.com.

Directions for use:

- Dilute with de-ionised water in accordance with the vehicle manufacturer's instructions.
- Pour into vehicle cooling system.
- Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook.
- Remove spills from paintwork immediately.

Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.
- Wash off any spillage on paintwork immediately.
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

14-11-2014