



XT2000 15W-40

Semi Synthetic

Recommended by Comma for applications requiring:

MB 229.1; MB228.3; VW 501 01, VW 505 00
ACEA A3/B4; API SL CF CG-4

Product Features:

- Semi synthetic, high performance 15W-40 oil, suitable for petrol and diesel vehicles including those with fuel injected and multivalved engines.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Typical Inspection Data:

| | |
|-----------------------|---------------|
| Density @ 20°C | 0.868 |
| Viscosity @ 100°C | 14.0 cSt |
| Viscosity @ 40°C | 100 cSt |
| Viscosity Index | 140 |
| Viscosity CCS @ -20°C | 4500 cP |
| T.B.N. | 10.0 mg KOH/g |
| Sulphated Ash Mass | 1.3% |
| Zinc | 0.12% |
| Calcium | 0.36% |
| Phosphorus | 0.12% |
| Colour | Brown |
| Flash Point | 230°C |
| Pour Point | -30°C |

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

10-10-2014