



Product Name:

Longlife 5W-30

Comma recommends this product for applications requiring:

GM-LL-A-025, GM-LL-B-025; MB 229.5; BMW LL-01; VW 502 00, VW 505 00; RN0700

ACEA A3/B4; API SL CF

Product Features:

- For GM, Vauxhall and Opel vehicles operating with longlife service intervals.
- Fully synthetic, high performance, 5W-30 oil, for GM/Vauxhall/Opel petrol and diesel vehicles operating under long life service regimes.
- Do not mix this oil with other types of oil, as the requirement for the long life service intervals will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest Application guide in store or online at www.CommaOil.com

Typical Inspection Data:

| | |
|--------------------------|--------------|
| Specific gravity at 20°C | 0.852 |
| Viscosity @ 100°C | 12.0 cSt |
| Viscosity @ 40°C | 70 cSt |
| Viscosity Index | 165 |
| Viscosity CCS @ -30°C | 6000 cP |
| T.B.N. | 9.5 mg KOH/g |
| Sulphated Ash Mass | 1.4% |
| Zinc | 0.11% |
| Calcium | 0.31% |
| Phosphorus | 0.10% |
| Colour | Brown |

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the day of the year, the last two figures the year.