COMMA

Technical Data Sheet



Pro-VLL 0W-30

Fully Synthetic

Recommended by Comma for applications requiring:

VW 503 00,
VW 506 00,
VW 506 01

Product Features:

- Fully synthetic, high performance fuel-economy promoting engine oil, developed specifically for diesel PD Volkswagen engines running on LongLife Service regime.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com.

Typical Inspection Data:

Density @ 20 °C	0.853
Viscosity @ 100 °C	9.5 cSt
Viscosity @ 40 °C	53 cSt
Viscosity Index	165
Viscosity CCS @ -35 °C	5900 cP
T.B.N.	9.7 mg KOH/g
Sulphated Ash Mass	1.2%
Zinc	0.14%
Calcium	0.28%
Phosphorus	0.12%
Colour	Amber
Flash Point	>200°C
Pour Point	-42°C

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

28-12-2016

Comma Oil & Chemicals Ltd.
Dering Way, Gravesend, Kent DA12 2QX, England.
Tel: +44 (0)1474 564311, Fax: +44 (0)1474 333000
Email: sales@commaoil.com www.CommaOil.com