



SAFETY DATA SHEET
SX 75W90 SYNTHETIC BASED GEAR OIL

Page 1

Issued: 16/02/2004

Revision No: 10

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: SX 75W90 SYNTHETIC BASED GEAR OIL

Product code: SX****

Company name: Comma Oil & Chemicals Ltd.

Dering Way

Gravesend

Kent

DA12 2QX

Tel: +44 01474 564311

Fax: +44 01474 333000

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: PHOSPHORIC ACID ESTERS, AMINE SALT 1-10%

[N] R51/53

- ALKENYL AMINE <1%
[Xn] R22; [C] R34; [Sens.] R43; [N] R50
- SUBSTITUTED THIADIAZOLE. <1%
[Sens.] R43

Contains: Hazardous ingredients present at or above regulatory disclosure limits

3. HAZARDS IDENTIFICATION

Main hazards: No significant hazard.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Do not induce vomiting. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol or polymer foam. Dry chemical powder. Carbon dioxide.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

[cont...]

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits

TWA (8 hr exposure limit): 5 mg/m³ for oil mist (OES)

Respiratory protection: Respiratory protection not required.

Hand protection: Gloves (oil-resistant).

Eye protection: Safety glasses.

Skin protection: Oil-resistant protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Gold-brown

Odour: Barely perceptible odour

Evaporation rate: Negligible

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: 104.0 mm²/s @ 40 C

Viscosity test method: ASTM D445

Flash point°C: 138

Relative density: 0.887 @ 20 C

pH: n/a

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat. Sources of ignition.

Materials to avoid: Oxidising agents.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil. Non-volatile. Floats on water.

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

13. DISPOSAL CONSIDERATIONS

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: -

Shipping name: "NOT SUBJECT TO ADR"

IMDG / IMO

UN no: -

IATA / ICAO

UN no: -

15. REGULATORY INFORMATION

Hazard symbols: No significant hazard.

Precautionary phrases: Contains alkenyl amine, substituted thiadiazole.. May produce an allergic reaction.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R22: Harmful if swallowed.

R34: Causes burns.

R43: May cause sensitisation by skin contact.

R50: Very toxic to aquatic organisms.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.