



Typical Inspection Data:

Colour	Grey/Black
Texture	Smooth
NLGI No.	2 (Medium)
Worked Penetration	265 - 295
Drop Point °C	>180
Sphere of use °C	-10 to 120
4 ball load	315Kgf
Oil separation 40°C, 168 hrs	<7%

CV Lith-Moly Grease

Product Features:

- Lithium-based grease, containing Molybdenum disulphide. Specially formulated for use in CV joints.
- High in extreme pressure additives to give long life under heavy loads.
- Chemically compatible with polymeric boot material.
- Includes a laminar solid lubricant which overcomes boundary lubrication.
- Good corrosion protection – Rust inhibited to protect bearing surfaces.

Directions for use:

- Never over pack the bearing.
- It is sound lubrication practice to remove the old grease before new grease is introduced. If used grease cannot be removed, Comma C V Lith-Moly grease is generally compatible with other lithium based greases. When mixed with other grease types, this grease should be satisfactory below an operating temperature of 80 °C.

Handling:

- Avoid extremes of temperature.
- Store under cover.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.

21-11-2014