



Typical Inspection Data:

| | |
|------------------------|-------------------------|
| Density @ 20 °C | 0.850 g/cm ³ |
| Viscosity @ 100 °C | 10.3 cSt |
| Viscosity @ 40 °C | 58 cSt |
| Viscosity Index | 169 |
| Viscosity CCS @ -30 °C | 5500 cP |
| T.B.N. | 7.0 mg KOH/g |
| Sulphated Ash Mass | 0.7% |
| Zinc | 0.09% |
| Calcium | 0.19% |
| Phosphorus | 0.08% |
| Colour | Brown |
| Flash Point | 230 °C |
| Pour Point | -36 °C |

Pro-Tech 5W-30

Fully Synthetic

Recommended by Comma for applications requiring:

PSA B71 2290
ACEA A5/B5, ACEA C2; API SN

Product Features:

- Fully synthetic, high performance 5W-30 low SAPS oil for modern petrol and diesel vehicles including those fitted with exhaust after-treatment units that require an ACEA C2 grade.
- Do not mix this oil with other types of oil, as the requirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

24-02-2017