

Technical Data Sheet



Typical Inspection Data:

| | |
|----------------|-------------------------|
| Density @ 20°C | 1.124 g/cm ³ |
| Appearance | Blue liquid |
| Boiling point | 168 °C |

Approx. Protection Levels:

| | |
|-----|--------|
| 33% | -18 °C |
| 50% | -36 °C |
| 60% | -52 °C |

Super Coldmaster - Concentrate

Recommended by Comma for applications requiring:

Conforms to BS 6580:2010, AFNOR NFR 15-601

Product Features:

- A Mono Ethylene Glycol (MEG) based engine coolant / anti-freeze concentrate.
- Suitable for use in all types of vehicle requiring an MEG coolant.
- Suitable for Ferrous and Aluminium engines.
- 2 years full protection.
- Helps prevent winter freezing and summer boil over. Also improves heat transfer.
- NAP (Nitrite, Phosphate and Amine) free.

Directions for use:

- Dilute with de-ionised water in accordance with the vehicle manufacturer's instructions.
- Pour into vehicle cooling system.
- Minor spills should be soaked up with absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.

Handling:

- Remove spills from paintwork immediately
- Keep away from foodstuffs and oxidising agents
- Store in airtight container
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product

Shelf life:

- 3 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 22.07.2024