

# Technical Data Sheet



## Typical Inspection Data:

Density @ 20°C	1.074 g/cm <sup>3</sup>
Appearance	Clear green/blue liquid

## Super Coldmaster - Ready to Use

### Ready to Use

Recommended by Comma for applications requiring:

Conforms to BS 6580:2010, AFNOR NFR 15-601

#### Product Features:

- A Mono Ethylene Glycol (MEG) based engine coolant.
- Suitable for use in all types of vehicle requiring an MEG coolant.
- Suitable for Ferrous and Aluminium engines.
- -36°C Winter protection / +45°C Summer protection.
- 2 years full protection.
- Helps prevent winter freezing and summer boil over. Also improves heat transfer.
- NAP (Nitrite, Phosphate and Amine) free.

#### Directions for use:

- Ready to use, but for maximum protection first drain and flush cooling system.
- For full protection do not mix with other fluids.
- Minor spills should be soaked up with absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.

#### Handling:

- Remove spills from paintwork immediately
- Keep away from foodstuffs and oxidising agents
- Store in airtight container
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product

#### Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

**UPDATED: 06.05.2025**