

## Technical Data Sheet



### Typical Inspection Data:

Density @ 20°C	1.132 g/cm <sup>3</sup>
Appearance	Clear yellow liquid
Boiling point	184 °C
Reserve Alkalinity	18 ml
Water Content	2.1 %wt
Reflective Index	1.436

### Approx. Protection Levels:

33%	-18 °C
50%	-36 °C
60%	-52 °C

## Xstream® G05® Antifreeze & Coolant Concentrate

Glysantin® G05® by BASF is approved by:

Chrysler (MS-9769), Ford North America (WSS-M97B51-A1), JCB (STD 00088), John Deere (JDM H 24), MTU (MTL 5048), Concentrate: BS 6580:2010

### Product Features:

- Heavy Duty ethylene glycol based antifreeze for use in vans and trucks
- Protects against corrosion, overheating and freezing
- Typical service life of up to 6,000 hours
- Safeguarded with bittering agent to help prevent accidental ingestion

### Handling:

- Dilute with de-ionised water in accordance with the vehicle manufacturer's instructions
- Pour into vehicle cooling system
- Do not mix different types of Antifreeze. If in doubt about product suitability, refer to vehicle handbook.
- Remove spills from paintwork immediately

### Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

**UPDATED: 06.05.2025**