

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	1.125 g/cm3
Appearance	Clear, Green
Boiling point	170 °C
Reserve Alkalinity	9.5 ml
Water Content	3.5 %wt
Reflective Index	1.432

Approx. Protection Levels:

33%	-18 °C
50%	-37 °C

Xstream® G64® Antifreeze & Coolant Concentrate

Glysantin® G64® by BASF is approved by:

Deutz (DQC CC-14), Deutz-Fahr, Huerlimann (vehicles built as from 04/2017), Jenbacher (TA 1000-0200), Lamborghini Tractors (vehicles built as from 04/2017), MAN Energy Solutions (MAN engine type MAN 175D, BASF-CW-GLY00G64-01), MWM (TR 2091), Volvo Cars (TR-31854114-002)

Product Features:

- Ethylene glycol based antifreeze and coolant with silicate based inhibitors
- Protects against corrosion, overheating and freezing
- Typical service life of up to 5 years
- Safeguarded with bittering agent to help prevent accidental ingestion

Directions for use:

1. Dilute with de-ionised water in accordance with the vehicle manufacturer's instructions Pour into vehicle cooling system.,
2. Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook.,
3. Remove spills from paintwork immediately

Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should be washed with soapy water and dried
- Wash off any spillage on paintwork immediately
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 06.05.2025