



## Typical Inspection Data:

Density @ 20°C	0.841 g/cm <sup>3</sup>
Viscosity @ 100°C (cSt)	9.7 cSt
Viscosity @ 40°C	50
Viscosity Index	183
Viscosity CCS @ -35°C (cP)	5500 cP
T.B.N (mg KOH/g)	8 mg KOH/g
Sulphated Ash Mass (%)	0.8 %
Zinc (%)	0.1 %
Colour	Brown
Phosphorus (%)	0.08 %
Flash Point (°C)	>200 °C
Pour Point (°C)	-42 °C
Calcium (%)	0.18 %

## ECO FE PLUS 0W-30

### Synthetic Technology

Recommended by Comma for applications requiring any of the following:

ACEA C2, API SN, Ford WSS-M2C950-A, STJLR.03.5007

#### Product Features:

- Synthetic technology, mid-SAPS engine oil specifically developed for Ford engines from 2014.
- Also suitable for modern Land Rover and Jaguar models.
- Designed for high fuel efficiency.
- Suitable for petrol and diesel vehicles.
- To ensure correct oil selection use Comma's latest application guide instore or online at [www.CommaOil.com](http://www.CommaOil.com)

#### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

#### Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 06.05.2026