

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	0.842 g/cm3
Viscosity @ 100°C (cSt)	8.0 cSt
Viscosity @ 40°C (cSt)	42 cSt
Viscosity Index	166
Viscosity CCS @ -35°C (cP)	5500 cP
T.B.N (mg KOH/g)	10.0 mg KOH/g
Sulphated Ash Mass (%)	0.8 %
Zinc (%)	0.09 %
Colour	Brown
Phosphorus (%)	0.08 %
Flash Point (°C)	>200 °C
Pour Point (°C)	-42 °C
Calcium (%)	0.13 %

ECO-PS 0W-20

Synthetic Technology

Recommended by Comma for applications requiring any of the following:

ACEA C5, API SP, PSA B71 2010

Product Features:

- Synthetic technology, high performance 0W-20 oil for modern petrol, diesel and hybrid vehicles...
- Specially formulated for the requirements of Stellantis/PSA cars requiring high engine protection with the latest PSA B71 2010 specification.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 06.05.2025