

# Technical Data Sheet



## Typical Inspection Data:

Density @ 20°C	0.833 g/cm <sup>3</sup>
Viscosity @ 100°C (cSt)	6.1 cSt
Viscosity @ 40°C	26.2
Viscosity Index	194
Colour	Straw
Phosphorus (%)	0.02 %
Flash Point (°C)	220 °C
Pour Point (°C)	-69 °C

## EXT Fluid

### Central Hydraulic Fluid

Recommended by Comma for applications requiring any of the following:

GM 89021185, GM 89021186, GM 1052884, GM 993294, GM 19329450, GM 19329451, GM 1940707, GM 89020661, Hyundai/Kia PSF-3, Hyundai/Kia PSF-4, Chrysler MS 5931, Fiat 9.55550-AG-1, Fiat 9.55550-AG-2, Fiat 9.55550-AG-3 ISO VG 22, Fiat 9.55550-AV4, Texaco Cold Climate Power Steering Fluid, Saab P/N 45 30 09 800, DiaQueen PSF, Pentosin CHF 7.1, Toyota Type EH, Nissan PSF-II, PSA S71 2710

#### Product Features:

- EXT Fluid is a special synthetic based hydraulic fluid suitable for central hydraulic systems, power steering and suspension level control systems.
- Also suitable for certain stability and traction control systems, hydrostatically driven fans, generators and air conditioning units, control of convertible car top covers and central locking systems.

#### Directions for use:

- Always follow the vehicle manufacturer's recommendations when adding EXT Fluid.
- Check vehicle handbook if in doubt.
- Keep fluid clean.
- Caution: Store only in its original container.
- Keep container clean and tightly closed.
- Do not refill container or use for other liquids.

#### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

#### Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

**UPDATED: 13.09.2024**