



## Typical Inspection Data:

Density @ 20°C	0.875 g/cm <sup>3</sup>
Viscosity @ 100°C (cSt)	14 cSt
Viscosity @ 40°C	129
Colour	Brown
Phosphorus (%)	0.02 %
Pour Point (°C)	-30 °C

## GEAR OIL EP80W-90 GL-5 Mineral

Recommended by Comma for applications requiring any of the following:

Recommended by Comma for certain applications where an 80W-90 or 85W-90 API GL-5, GL-4 oil is specified. Suitable for use where the following specifications are called for: API GL-5, FORD WSS M2C917-A, MB 235.0

### Product Features:

- Extreme pressure gear oil for manual gearboxes.
- Recommended by Comma for applications requiring an 80W-90 or 85W-90 API GL-4 oil.
- To ensure correct oil selection check Comma's latest application guide instore or online at [www.CommaOil.com](http://www.CommaOil.com)

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

### Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 22.01.2026