

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	0.84 g/cm ³
Viscosity @ 100°C (cSt)	6.4 cSt
Viscosity @ 40°C	33
Colour	Red
Phosphorus (%)	0.02 %
Pour Point (°C)	-45 °C

MVATF Plus Fully Synthetic

Recommended by Comma for applications requiring any of the following:

Recommended by Comma for certain Mercedes, Hyundai, Kia, Vauxhall/Opel and Ford automatic transmissions. Suitable for use where the following specifications are called for:; Aisin Warner AW-1, Allison C-4, ATF J3, ATF Red-1K, ATF SP, ATF SP-II, ATF SP-III, ATF SP-IV, BMW 81 22 9 400 272, BMW 83 22 2 152 426, BMW 83 22 2 289 720 (ATF3+), BMW 83 22 2 305 397 (ATF3), BMW 83 22 2 355 599 (ATF6), Chrysler MS 7176E (ATF +3), Chrysler MS 9602 (ATF +4), Dexron® (H), Dexron® II, Dexron® II D, Dexron® IIE, Dexron® IIE + Mercon, Dexron® III, Dexron® III (G), Dexron® III +, Dexron® III + Mercon, Dexron® VI, DiaQueen ATF-PA, ETL 7045E, ETL 8072B, Ford ESP-M2C166-H, Ford M2C138-CJ, Ford M2C195-A, Ford WSS-M2C202-B, Ford WSS-M2C922-A1, Ford WSS-M2C938-A (power steering), GM 1940767, GM 1940771, Honda ATF DW-1, Honda ATF Type 3.0, Honda ATF Type 3.1, Honda ATF-Z1, JWS 3309, JWS 3314 + Matic D (1:2), JWS 3324 (ATF WS), LA-2634, LT71141, M-1375.4, M-III, Mazda FZ, MB 236.10, MB 236.11, MB 236.12, MB 236.14, MB 236.41, MB 236.5, Mercon, Mercon LV, Mercon SP, Mercon V, N402, Nissan Matic D, Nissan Matic J, Nissan Matic K, Nissan Matic S, Nissan Matic W, NWS 9638 T-5, SP-IV-RR, Special ATF, M-V (Type M5), Toyota Type T, Toyota Type T-II, Toyota Type T-IV, Type A Suffix A, Volvo 1161540, VW G 052 162, VW G 052 533, VW G 052 990, VW G 055 005, VW G 055 025, VW G 055 540, VW G 060 162, ZF Lifeguardfluid8, ZF TE-ML 11A, ZF TE-ML 11B

Product Features:

- Offers excellent frictional stability, anti-shudder & anti-wear properties
- Suitable for automatic transmissions and power steering systems for many European, American and Asian vehicles
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

UPDATED: 06.05.2025

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 06.05.2025