



## Typical Inspection Data:

Density @ 20°C	0.865 g/cm <sup>3</sup>
Viscosity @ 100°C (cSt)	16.5 cSt
Viscosity @ 40°C	104 cSt
Colour	Light Straw
Phosphorus (%)	0.02 %
Pour Point (°C)	-42 °C

## SX75W-90 GL-4

### Semi Synthetic

Recommended by Comma for applications requiring any of the following:

Recommended by Comma for certain applications where a 75W-90, 80W-90 or 85W-90 API GL-4 oil is specified. Suitable for use where the following specifications are called for: API GL-4, Ford M2C175-A, API GL-3 (75W-85 & 75W-90), API GL-3 (75W-85 & 75W-90, API GL-4, Ford M2C175-A

#### Product Features:

- Suitable for modern five and six speed gear boxes and differentials.
- Recommended by Comma for applications requiring a 75W-90, 80W-90 or 85W-90 API GL-4 oil.
- To ensure correct oil selection use Comma's latest application guide instore or online at [www.CommaOil.com](http://www.CommaOil.com)

#### Handling:

- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

#### Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 09.04.2026