



## Typical Inspection Data:

Colour

Milky White Liquid

## Tyre Seal

### Product Features:

- Repairs punctures & re-inflates – fast.
- Suitable for holes up to 3mm/0.1 inch diameter and tyre sizes up to 41cm/16 inches.
- Do not apply to disrupted tyres or tyres which have slipped from the rim.
- Do not apply to air-pressure monitored tyres.

### Directions for use:

1. Remove foreign object from the tyre.
2. Rotate the tyre's valve on 3 or 9 o'clock position and deflate the tyre entirely.
3. Shake can before use and in winter - heat it using the warmth of your hand.
4. Screw the filling hose to the tyre's valve and entirely purge Tyre Seal 400ml into the tyre.
5. After that, drive to the next car service center at a maximum speed of 50 km/h /30 mph. It is necessary to check the tyre's air-pressure after 15km /10 miles.

### Handling:

- Always advise your tyre repairer that you have used Tyre Seal and show them the can
- Caution pressurised container: protect from sunlight and other heat sources
- Refer to Material Safety Data Sheet

### Shelf life:

- 3 years from date of manufacture
- Manufacture date can be identified as follows:

1st Letter-Year		2nd Letter-Month		2 Numbers-Day	Time
2020	A	Jan	A	Number denotes the day of the Month	Time in 24 hour format: hour and minutes e.g. 16:05
2021	B	Feb	B		
2022	C	Mar	C		
2023	D	Apr	D		
2024	E	May	E		

**UPDATED: 28.05.2026**

2025	F	Jun	F		
2026	G	Jul	G		
2027	H	Aug	H		
2028	J	Sep	J		
2029	K	Oct	K		
2030	L	Nov	L		
2031	M	Dec	M		

**UPDATED: 28.05.2026**