

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	1.124 g/cm3
Appearance	Blue liquid
Boiling point	168 °C

Approx. Protection Levels:

33%	-18 °C
50%	-36 °C
60%	-52 °C

Super Coldmaster - Concentrate

Recommended by Comma for applications requiring:

Conforms to BS 6580:2010, AFNOR NFR 15-601

Product Features:

- A Mono Ethylene Glycol (MEG) based engine coolant / anti-freeze concentrate.
- Suitable for use in all types of vehicle requiring an MEG coolant.
- Suitable for Ferrous and Aluminium engines.
- 2 years full protection.
- Helps prevent winter freezing and summer boil over. Also improves heat transfer.
- NAP (Nitrite, Phosphate and Amine) free.

Directions for use:

- Dilute with de-ionised water in accordance with the vehicle manufacturer's instructions.,
- Pour into vehicle cooling system.,
- Minor spills should be soaked up with absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.

Handling:

- Remove spills from paintwork immediately
- Keep away from foodstuffs and oxidising agents
- Store in airtight container
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product

Shelf life:

- 3 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 06.05.2025