



Typical Inspection Data:

Density @ 20°C	1.124 g/cm ³
Appearance	Clear Violet Liquid
Boiling point	177 °C
Reserve Alkalinity	10 ml
Water Content	2.3 %wt
Reflective Index	1.434

Approx. Protection Levels:

33%	-18 °C
50%	-36 °C
60%	-52 °C

Xstream® G30® Antifreeze & Coolant Concentrate

Glysantin® G30® by BASF is approved by:

Audi/Bentley/Lamborghini/Seat/Skoda/VW Porsche (TL 774-D/F), DAF (MAT 74002), Deutz (DQC CB-14), MAN Truck and Bus (MAN 324 Typ SNF), Mercedes-Benz Trucks & Buses (DTFR 29C110), SETRA (DTFR 29C110), Mini (BMW LC-07), Siemens (wind power)

Product Features:

- Ready to use ethylene glycol based antifreeze & coolant with OAT inhibitors.
- Protects against corrosion, overheating and freezing.
- Typical service life of up to 5 years
- Safeguarded with bittering agent to help prevent accidental ingestion.

Directions for use:

1. Dilute with deionised water in accordance with the vehicle manufacturer's instructions.,
2. Pour into vehicle cooling system.,
3. Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook.,
4. Remove spills from paintwork immediately

Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should be washed with soapy water and dried
- Wash off any spillage on paintwork immediately
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 22.01.2026