



Typical Inspection Data:

Density @ 20°C	1.124 g/cm ³
Appearance	Clear violet liquid
Boiling point	177 °C
Reserve Alkalinity	10 ml
Water Content	2.6 %wt
Reflective Index	1.434

Approx. Protection Levels:

33%	-18 °C
50%	-36 °C
60%	-52 °C

Xstream® G40® Antifreeze & Coolant Concentrate

Glysantin® G40® by BASF is approved by:

Audi/Bentley/Bugatti/Lamborghini/Seat/Skoda/VW/Porsche vehicles (TL774-G), Liebherr (MIN LH-01-COL3A), Cummins (CES 14603), Deutz (DQC CC-14), MAN Trucks & Buses (MAN 324 Typ Si-OAT), Mercedes-Benz Cars (MB-Approval 325.6), Mercedes-Benz Truck & Buses (DTFR 29C120), MTU (MTL 5048)

Product Features:

- Ethylene glycol based antifreeze with Si-OAT (Silicated Organic Additive Technology) inhibitors.
- Protects against corrosion, overheating and freezing.
- Safeguarded with bittering agent to help prevent accidental ingestion.

Directions for use:

1. Dilute with deionised water in accordance with the vehicle manufacturer's instructions
2. Pour into vehicle cooling system
3. Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook
4. Remove spills from paintwork immediately

Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should be washed with soapy water and dried
- Wash off any spillage on paintwork immediately
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 28.05.2026