

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	1.074 g/cm ³
Appearance	Clear violet liquid
Approx. protection	-36 °C

Xstream® G40® Antifreeze & Coolant Ready Mixed

Glysantin® G40® by BASF is approved by:

TL774-G - from 2005, Min of LH-01-COL3A - Liebherr., Cummins (CES 14603), Deutz (DQC CC-14), MAN 324 Si-OAT from 12-2011, MB-326.5 - Mercedes & Smart Cars, MB-326.6 Mercedes Trucks, MTU (MTL 5048), Porsche from 2010 (Boxster, Cayman, Cayenne, Panamera), Ready Mix BS 6580:2010

Product Features:

- Ready to use ethylene glycol based antifreeze with Si-OAT (Silicated Organic Additive Technology) inhibitors
- Protects against corrosion, overheating and freezing
- Typical service life of up to 5 years
- Safeguarded with bittering agent to help prevent accidental ingestion

Directions for use:

1. Do not dilute- pour directly into vehicle cooling system.,
2. Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook.,
3. Remove spills from paintwork immediately

Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should be washed with soapy water and dried
- Wash off any spillage on paintwork immediately
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 06.05.2025