

## Technical Data Sheet



### Typical Inspection Data:

Density @ 20°C	1.074 g/cm <sup>3</sup>
Appearance	Green
Approx. protection	-36 °C

## Xstream® G48® Antifreeze & Coolant Ready Mixed Concentrate

Glysantin® G48® by BASF is approved by:

Audi/ Seat/ Skoda / VW built until 1996 (TL774-C), BMW (BMW GS94000), Deutz (DQC CA-14), Jenbacher (Ta-Nr.1000-0201), Liebherr (Minimum LH-00-COL3A), MAN until 11/2011 (MAN 324 NF), MAN Diesel & Turbo (Liste 3.3.7), Mayback (MB-Approval 326.0), Mercedes Benz vehicles built until 2013 (MB-Approval 326.0), MINI (BMW GS94000), Rolls-Royce from 1998 (BMW GS94000), MTU (MTL 5048), MWM (0199-99- 2091 DE), Opel/Vauxhall vehicles built up to 2005 (B 040 0240), Porsche (vehicles built up until 1995), Same Deutz Fahr Group, Saab (690 1599), Smart vehicles built until 2013 (MB-Approval 326.0), Smart vehicles built until 2013 (MB-Approval 325.0), Tesla, Volvo Truck built until 2005, Van Hool, Zastava, Ready Mix BS 6580:2010

### Product Features:

- Ready to use ethylene glycol based antifreeze and coolant with silicate based inhibitors
- Protects against corrosion, overheating and freezing
- Typical service life up to 3 years
- Safeguarded with bittering agent to help prevent accidental ingestion

### Directions for use:

1. Do not dilute- pour directly into vehicle cooling system
2. Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook
3. Remove spills from paintwork immediately

### Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should be washed with soapy water and dried
- Wash off any spillage on paintwork immediately
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product

### Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

**UPDATED: 06.05.2025**