



Typical Inspection Data:

Density @ 20°C	1.074 g/cm ³
Appearance	Green
Approx. protection	-36 °C

Xstream® G48® Antifreeze & Coolant Ready Mixed Concentrate

Glysantin® G48® by BASF is approved by:

Audi/Seat/Skoda/VW (TL774-C), BMW & MINI (BMW LC-87), Deutz (DQC CA-14), Jenbacher (TA 1000-0200), Liebherr (Minimum LH-00-COL3A), MAN Energy Solutions (Liste 3.3.7), MAN Truck & Bus (MAN 324 Typ NF), Mercedes-Benz Cars (MB-Approval 326.0), Mercedes-Benz Trucks & Buses (DTFR 29D100), Rolls-Royce (BMW LC-87), MWM (TR 2091), Opel/Vauxhall vehicles (B 040 0240), Porsche, Same, Deutz-Fahr, Saab (690 1599), Smart (MB Approval 326.0), Volvo Trucks (TR 1286083), Van Hool, Zastava

Product Features:

- Ethylene glycol based antifreeze and coolant with silicate based inhibitors.
- Protects against corrosion, overheating and freezing.
- Typical service life of up to 3 years.
- Safeguarded with bittering agent to help prevent accidental ingestion.

Directions for use:

1. Do not dilute- pour directly into vehicle cooling system
2. Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook
3. Remove spills from paintwork immediately

Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should be washed with soapy water and dried
- Wash off any spillage on paintwork immediately
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 22.01.2026