



## Typical Inspection Data:

Density @ 20°C	1.075 g/cm <sup>3</sup>
Appearance	Clear, Green
Approx. protection	-37 °C

## Xstream® G64® Antifreeze & Coolant Ready Mixed

Glysantin® G64® by BASF is approved by:

Deutz (DQC CC-14), Deutz-Fahr, Huerlimann (vehicles built as from 04/2017), Jenbacher (TA 1000-0200), Lamborghini Tractors (vehicles built as from 04/2017), MAN Energy Solutions (MAN engine type MAN 175D, BASF-CW-GLY00G64-01), MWM (TR 2091), Same, Volvo Cars (TR-31854114-002)

### Product Features:

- Ethylene glycol based antifreeze and coolant with silicate based inhibitors.
- Protects against corrosion, overheating and freezing.
- Typical service life of up to 5 years
- Safeguarded with bittering agent to help prevent accidental ingestion.
- To ensure correct antifreeze & coolant selection check Comma's latest application guide in store or online at [www.CommaOil.com](http://www.CommaOil.com).

### Directions for use:

1. Do not dilute- pour directly into vehicle cooling system
2. Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook
3. Remove spills from paintwork immediately

### Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should be washed with soapy water and dried
- Wash off any spillage on paintwork immediately
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product

### Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 09.04.2026