

# Technical Data Sheet



## Typical Inspection Data:

Density @ 20°C	1.06 g/cm <sup>3</sup>
Viscosity @ 100°C (cSt)	2.1 cSt
Viscosity CCS @ - 40°C	700
Colour	Colourless to amber
Equilibrium Reflux Boiling Point	265 °C
Wet Equilibrium Reflux Boiling Point	170 °C
pH (50% EtOH)	8.1

## DOT 4 ESP Synthetic Brake & Clutch Fluid

### Synthetic Brake & Clutch Fluid

Recommended by Comma for applications requiring any of the following:

FMVSS 116 DOT 4, ISO 4925 (Classes 3, 4 & 6), SAE J1703, SAE J1704

#### Product Features:

- Specially formulated for use in cars with ABS.
- For improved braking and faster anti-skid reaction at low temperatures.
- Can be mixed safely with DOT 4 fluids.

#### Directions for use:

- **IMPORTANT** - Follow vehicle manufacturer's recommendations.
- Keep Brake Fluid clean and dry.
- Store in original container only.
- Caution: Do not refill container and do not use for other liquids.
- Take care not to spill on paintwork. If spilt wash off with plenty of water. Do not rub.
- All brake fluids absorb moisture and therefore they must be checked or changed regularly.

#### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

#### Shelf life:

- 3 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

**UPDATED: 06.05.2025**