

## Technical Data Sheet



### Typical Inspection Data:

Density @ 20°C	1.068 g/cm <sup>3</sup>
Viscosity @ 100°C (cSt)	2.2 cSt
Viscosity CCS @ - 40°C	850
Colour	Colourless to amber
Equilibrium Reflux Boiling Point	278 °C
Wet Equilibrium Reflux Boiling Point	183 °C
pH (50% EtOH)	7.3

## DOT 5.1 Synthetic Brake and Clutch Fluid

### Synthetic Brake Fluid

Recommended by Comma for applications requiring any of the following:

FMVSS 116 DOT 4, ISO 4925 (Classes 3, 4 & 6)

#### Product Features:

- The highest quality brake fluid specially formulated for use in today's high performance vehicles. Minimum wet boiling point of 180°C - ideal for all ABS systems
- Non-Silicone based can be mixed safely with DOT 3 & DOT 4 Fluids

#### Directions for use:

- **IMPORTANT** - Follow vehicle manufacturer's recommendations
- Keep Brake Fluid clean and dry
- Store in original container only
- Keep container clean and tightly closed to prevent water absorption
- Caution: Do not refill container and do not use for other liquids.
- Take care not to spill on paintwork. If spilt wash off with plenty of water. Do not rub
- All brake fluids absorb moisture and therefore they must be checked or changed regularly

#### Handling:

- Avoid extremes of temperature
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

#### Shelf life:

- 3 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

**UPDATED: 06.05.2025**