

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	0.847 g/cm ³
Viscosity @ 100°C (cSt)	8.4 cSt
Viscosity @ 40°C	46
Viscosity Index	161
Viscosity CCS @ -30°C (cP)	3800 cP
T.B.N (mg KOH/g)	8.1 mg KOH/g
Sulphated Ash Mass (%)	0.8 %
Zinc (%)	0.1 %
Colour	Brown
Phosphorus (%)	0.09 %
Flash Point (°C)	230 °C
Pour Point (°C)	-39 °C
Calcium (%)	0.18 %

ECO-F 5W-20

Fully Synthetic

Official Approvals:

STJLR.03.5004

Recommended by Comma for applications requiring any of the following:

ACEA C5, API SN, API SN-RC, FORD WSS M2C948-B, WSS M2C948-A, WSS-M2C925-B, WSS-M2C925-A, ILSAC GF-5

Product Features:

- Fully synthetic, high performance 5W-20 oil suitable for use in the latest Ford EcoBoost engines.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 01.07.2025