

# Technical Data Sheet



## Typical Inspection Data:

Density @ 20°C	0.84 g/cm <sup>3</sup>
Viscosity @ 100°C (cSt)	13.3 cSt
Viscosity @ 40°C	76
Viscosity Index	179
Viscosity CCS @ -35°C (cP)	6000 cP
T.B.N (mg KOH/g)	10.1 mg KOH/g
Sulphated Ash Mass (%)	1.1 %
Zinc (%)	0.12 %
Colour	Brown
Phosphorus (%)	0.1 %
Flash Point (°C)	230 °C
Pour Point (°C)	-45 °C
Calcium (%)	0.26 %

## ECO-MB 0W-40

### Fully Synthetic

Recommended by Comma for applications requiring any of the following:

ACEA A3/B4, API SN, MB 226.5, Porsche A40, Ford WSS-M2C937-A, RN 0700/0710

#### Product Features:

- Fully synthetic, high performance 0W-40 engine oil, for petrol and diesel vehicles including those with fuel injected and multivalved engines.
- Do not mix this oil with other types of oil, as the requirement for exhaust after-treatment protection will no longer be guaranteed.

#### Handling:

- Avoid extremes of temperature
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

#### Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

**UPDATED: 06.05.2025**