

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	0.843 g/cm3
Viscosity @ 100°C (cSt)	9.5 cSt
Viscosity @ 40°C	50
Viscosity Index	177
Viscosity CCS @ -35°C (cP)	5900 cP
T.B.N (mg KOH/g)	10.7 mg KOH/g
Sulphated Ash Mass (%)	0.8 %
Zinc (%)	0.08 %
Colour	Brown
Phosphorus (%)	0.08 %
Flash Point (°C)	>210 °C
Pour Point (°C)	-48 °C
Calcium (%)	0.11 %

ECO-P 0W-30

Fully synthetic

Recommended by Comma for applications requiring any of the following:

ACEA C2, PSA B71 2312

Product Features:

- Fully synthetic, high performance fuel-economy promoting engine oil, developed specifically for modern petrol and diesel PSA engines
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 06.05.2025