



Typical Inspection Data:

Density @ 20°C	0.842 g/cm ³
Viscosity @ 100°C (cSt)	7.1 cSt
Viscosity @ 40°C	36
Viscosity Index	164
Viscosity CCS @ -35°C (cP)	5200 cP
T.B.N (mg KOH/g)	7.2 mg KOH/g
Sulphated Ash Mass (%)	0.7 %
Zinc (%)	0.08 %
Colour	Brown
Phosphorus (%)	0.07 %
Flash Point (°C)	230 °C
Pour Point (°C)	-36 °C
Calcium (%)	0.13 %

ECO-T 0W-16 Synthetic Technology

Recommended by Comma for applications requiring any of the following:

API SP RC, ILSAC GF-6B

Product Features:

- Synthetic technology, low viscosity engine oil recommended for some of the latest hybrid plug-in and hybrid-electric cars.
- Provides excellent fuel economy and engine durability.
- Specifically developed to minimise low speed pre-ignition (LSPI).
- To ensure correct oil selection check Comma's latest application guide instore or online at www.CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 22.01.2026