

# Technical Data Sheet



## Typical Inspection Data:

Density @ 20°C	0.84 g/cm <sup>3</sup>
Viscosity @ 100°C (cSt)	12.1 cSt
Viscosity @ 40°C	61
Viscosity Index	200
Viscosity CCS @ -35°C (cP)	5900 cP
T.B.N (mg KOH/g)	8.2 mg KOH/g
Sulphated Ash Mass (%)	0.8 %
Zinc (%)	0.1 %
Colour	Amber
Phosphorus (%)	0.08 %
Flash Point (°C)	>200 °C
Pour Point (°C)	-48 °C
Calcium (%)	0.17 %

## ECO-VG 0W-30

### Fully Synthetic

Recommended by Comma for applications requiring any of the following:

ACEA C3, VW 504 00, VW 507 00, PORSCHE C30

#### Product Features:

- Fully synthetic engine oil exceeding 5W-30 VW 504/507 fuel efficiency requirements by over 25%.
- Designed to contain mid SAPS for enhanced CAT and DPF protection.
- To ensure correct oil selection use Comma's latest application guide instore or online at [www.CommaOil.com](http://www.CommaOil.com)

#### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

#### Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

**UPDATED: 06.05.2025**