

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	0.85 g/cm ³
Viscosity @ 100°C (cSt)	14.5 cSt
Viscosity @ 40°C	89
Viscosity Index	170
Viscosity CCS @ -30°C (cP)	6000 cP
T.B.N (mg KOH/g)	10 mg KOH/g
Sulphated Ash Mass (%)	1.1 %
Zinc (%)	0.12 %
Colour	Brown
Phosphorus (%)	0.12 %
Flash Point (°C)	210 °C
Pour Point (°C)	-39 °C
Calcium (%)	0.36 %

SYNER-G 5W-40 Synthetic Technology

Official Approvals:

VW 502 00, VW 505 00, MB-Approval 229.3

Recommended by Comma for applications requiring any of the following:

ACEA A3/B4, API SN/CF, MB 229.1, MB 226.5, RN0700, RN0710

Product Features:

- Synthetic technology, high performance 5W-40 oil, for petrol and diesel vehicles including those with fuel injected and multivalved engines
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 06.05.2025