



## Typical Inspection Data:

Density @ 20°C	0.844 g/cm <sup>3</sup>
Viscosity @ 100°C (cSt)	10.2 cSt
Viscosity @ 40°C	54
Viscosity Index	180
Viscosity CCS @ -35°C (cP)	6000 cP
T.B.N (mg KOH/g)	10 mg KOH/g
Sulphated Ash Mass (%)	1.1 %
Zinc (%)	0.12 %
Colour	Brown
Phosphorus (%)	0.1 %
Flash Point (°C)	220 °C
Pour Point (°C)	-42 °C
Calcium (%)	0.26 %

## VOLTECH 0W-30 Synthetic Technology

Recommended by Comma for applications requiring any of the following:

ACEA A5/B5, API SL

### Product Features:

- Synthetic technology high performance 0W-30 oil for modern petrol and diesel vehicles offering improved fuel economy benefits of an ACEA A5/B5 oil.
- To ensure correct oil selection use Comma's latest application guide instore or online at [www.CommaOil.com](http://www.CommaOil.com)

### Handling:

- Avoid extremes of temperature
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

### Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

**UPDATED: 22.01.2026**