

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	0.844 g/cm ³
Viscosity @ 100°C (cSt)	10.2 cSt
Viscosity @ 40°C	54
Viscosity Index	180
Viscosity CCS @ -35°C (cP)	6000 cP
T.B.N (mg KOH/g)	10 mg KOH/g
Sulphated Ash Mass (%)	1.1 %
Zinc (%)	0.12 %
Colour	Brown
Phosphorus (%)	0.1 %
Flash Point (°C)	220 °C
Pour Point (°C)	-42 °C
Calcium (%)	0.26 %

VOLTECH 0W-30 Synthetic Technology

Recommended by Comma for applications requiring any of the following:

ACEA A5/B5, API SL

Product Features:

- Synthetic technology, high performance 0W-30 oil, for modern petrol and diesel vehicles, offering improved fuel economy benefits of an ACEA A5/B5 oil.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 06.05.2025