

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	0.845 g/cm ³
Viscosity @ 100°C (cSt)	7.5 cSt
Viscosity @ 40°C	36
Colour	Red
Phosphorus (%)	0.01 %
Pour Point (°C)	-45 °C

AQ3™ Semi Synthetic

Recommended by Comma for applications requiring any of the following:

Recommended by Comma for certain applications requiring Dexron® III/IIIE/IIID/II. Suitable for use where the following specifications are called for: Dexron® II, Dexron® II D, Dexron® IIE, Dexron® III, Fiat 9.55550-SA1, PSA 9979 A4

Product Features:

- Protects against foaming, corrosion, oxidation and wear.
- Provides a quiet and smooth gear shift.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 06.05.2025